

USR5637, USR065637 & USR805637 56K* USB MODEM

ANALOG

The USRobotics 56K* USB Modem delivers the performance and reliability USRobotics is known for, in a compact, flexible form factor. This controller-based modem integrates powerful communications processing functions into the modem itself, for assured performance without sapping your computer's processing power. It is also broadly compatible across major operating systems including Linux, Windows and Macintosh. Quick Connect reduces your connection time to get you online quicker, and V.PCM Upstream provides 50% greater upload speeds — perfect for sending e-mail messages with large attachments. Also supports USRobotics Modem on Hold application to screen incoming voice calls while online, and to answer calls without losing your internet connection — no second phone line is needed!†

USRobotics®



High-performance streamlined

USB convenience and ease of use

- Simple USB Plug and Play installation
- Hot-swappable (installs/uninstalls automatically)
- Bus-powered so it doesn't require an external power supply

Advanced features and functionality

- Send and receive faxes through your computer while running other applications
- Supports group faxing and timed faxing
- Permanently store preferred modem default settings

Get the speed you need

- Quick Connect reduces the time it takes to establish your dial-up Internet connection.
- Need to send digital pictures or a large presentation? V.92 lets you send attachments up to 50% faster!

Powerful Management Tools

- USRobotics Modem on Hold application lets you:
 - Screen incoming calls so you can take the important ones†
 - Take calls while online without dropping your Internet connection — there's no need for a second phone line


Software Upgradable

- Firmware upgradable and downloadable software ensure that this modem will continue to meet your changing needs

Excellent Compatibility

- Compatible with most major operating systems, Windows, Linux and Macintosh





MODELS USR5637, USR065637 & USR805637 56K* USB MODEM



SPECIFICATIONS & STANDARDS

GENERAL

- Data: V.92, V.90, V.34, V.32bis, V.32, V.22bis, V.22, V.23, and V.21
- Data Error Control/Compression: V.44/V.42/V.42bis and MNP2-4/5
- Fax: EIA 578 (Class 1) with V.17, V.29, V.27ter, Group 3
- V.80 video conferencing support
- DTE interface: USB Version 2.0
- USB powered
 - Typical current from USB supply = 240 mA (1.2W)
 - Maximum current from USB supply = 360 mA (1.8W)

PHYSICAL

- 2 LEDs: Power, Data
- Phone line interface: One RJ-11 socket
- Caller ID support (requires service from your local phone company; Caller ID may not be supported in some countries)

ENVIRONMENTAL

- Temperature:
 - Operating Temperature conditions: 0 to 50 degrees C
 - Non-Operating Temperature conditions: -20 to 70 degrees C
- Humidity: Operating Humidity conditions:
 - 20% to 80% non-condensing
 - Non-Operating Humidity conditions: 5% to 95% non-condensing

REGULATORY

- FCC approved
- IC approved
- UL/CUL listed
- TBR-21

PACKAGE DIMENSIONS/WEIGHT

- 7.88 x 6 x 1.38 in (19.7 x 15.3 x 3.5 cm)
- .5 lb / .23 kg

PRODUCT DIMENSIONS

- 3.88 x 1.5 x .88 in (9.86 x 3.81 x 2.24cm)
- 0.26 lb (0.12 kg)

LANGUAGE SUPPORT

- **Retail box:** English, French, German, Greek, Italian, Spanish
- **Installation guide:** English, French, German, Greek, Italian, Spanish
- **CD ROM User Guide:** English, French, German, Greek, Italian, Spanish

MINIMUM SYSTEM REQUIREMENTS

- Windows® 2000/XP/Vista™, Mac 10.4 or later and Linux 2.4.20 kernel or higher
- Intel Pentium III 600 MHz or equivalent, 128 MB RAM, 5 MB hard drive space
- USB port
- 2x or better CD-ROM drive
- Analogue phone line

PACKAGE CONTENTS

- USRobotics 56K* USB Modem
- Phone cord
- Quick Installation Guide
- Installation Essentials CD-ROM: drivers for Windows/Macintosh/Linux, user's guide, data/fax software (Windows only), and USRobotics Modem on Hold application (software requires Windows 2000 or higher)

WARRANTY

- 2-year limited manufacturer warranty from date of purchase

* Capable of receiving at up to 56 Kbps and sending at up to 48 Kbps (or 31.2 Kbps with V.90 server). Due to FCC regulations on power output, receiving speeds are limited to 53.3 Kbps. Actual speeds may vary. V.92 and V.90 features require compatible phone service and support from your Internet Service Provider (ISP). USRobotics modems featuring V.92 enhancements are backward compatible and will negotiate the highest possible speed when connecting to an ISP.

† Call Waiting service required for using USRobotics Modem on Hold application and Modem on Hold. Call Waiting/ Caller ID service required for utilizing Caller ID capability.

For connection to the Public Switched Telephone Network (PSTN)

USRobotics®
www.usr.com

IC Approved
Approuvé par IC

